مؤسسة رمز ركاز الجودة للتجارة
Ramz Rikaz Al Joudah Trading Est.
C.R. No: 7055068394
VAT No: 312849650600003
4620 Street No. 10
3602 Al Jazirah Dist.
Riyadh 14262
Saudi Arabia
السجل التجاري: ٧٠٥٥٠٦٨٣٩٤
الرقم الضريبي: ٣١٢٨٤٩٦٥٠٦٠٠٠٠٣
٤٦٢٠ شارع رقم ١٠
٣٦٠٢ حي الجزيرة
الرياض ١٤٢٦٢
المملكة العربية السعودية
www.rjc.sa - info@rjc.sa

Datasheet

Rental Zoomlion ZS1012HA-Li Scissor Lift

Brand: Zoomlion



The **Zoomlion ZS1012HA-Li** electric scissor lift delivers reliable elevated access for indoor and outdoor maintenance, installation, and construction tasks.

- **Working Height:** 11.8 m
- **Platform Capacity:** 350 kg
- **Power Type:** Electric (Li-ion battery)
- **Platform Extension:** 0.91 m

www.rjc.sa - info@rjc.sa

مؤسسة رمز ركاز الجودة للتجارة
Ramz Rikaz Al Joudah Trading Est.

C.R. No: 7055068394
VAT No: 312849650600003
4620 Street No. 10
3602 Al Jazirah Dist.
Riyadh 14262
Saudi Arabia

السجل التجاري: ٧٠٥٥٠٦٨٣٩٤
الرقم الضريبي: ٣١٢٨٤٩٦٥٠٦٠٠٠٠٣
٤٦٢٠ شارع رقم ١٠
٣٦٠٢ حي الجزيرة
الرياض ١٤٢٦٢
المملكة العربية السعودية

Zoomlion ZS1012HA-Li Electric Scissor Lift

The **Zoomlion ZS1012HA-Li** is a robust electric scissor lift engineered by **Zoomlion Access** for efficient elevated work in a variety of settings. Its compact design and lithium-ion power make it suitable for both indoor and outdoor applications where quiet, emission-free operation is required.

Typical Applications

This scissor lift is well-suited for tasks that demand safe and stable access at height, including:

- General construction and finishing work
- Facility maintenance and repairs
- Electrical, HVAC, and plumbing installations
- Warehouse and logistics operations

Key Operational Features

The ZS1012HA-Li incorporates several features that enhance productivity and operator safety:

- Permanent magnet synchronous motor for energy efficiency and responsive control
- Lithium-ion battery with long service life and cold-weather capability
- Proportional controls for precise positioning
- Active pothole protection system for enhanced stability
- Emergency descent system and stop button for safe operation
- Fold-down handrails and self-closing entry gate for convenience

Equipment Inquiries

For more information about the Zoomlion ZS1012HA-Li scissor lift, including rental availability and terms, please contact our team.

مؤسسة رمز ركاز الجودة للتجارة
Ramz Rikaz Al Joudah Trading Est.
C.R. No: 7055068394
VAT No: 312849650600003
4620 Street No. 10
3602 Al Jazirah Dist.
Riyadh 14262
Saudi Arabia
السجل التجاري: ٧٠٥٥٠٦٨٣٩٤
الرقم الضريبي: ٣١٢٨٤٩٦٥٠٦٠٠٠٣
٤٦٢٠ شارع رقم ١٠
٣٦٠٢ حي الجزيرة
الرياض ١٤٢٦٢
المملكة العربية السعودية
www.rjc.sa - info@rjc.sa

Technical Specifications

Rental Zoomlion ZS1012HA-Li Scissor Lift

Specification	Value
Manufacturer	Zoomlion Access
Country of Origin	China
Working Height	11.80 m
Platform Height	9.80 m
Platform Height (Stowed)	1.39 m
Platform Length	2.30 m
Platform Width	1.12 m
Platform Extension	0.91 m
Overall Height (Rails Up)	2.53 m
Overall Height (Rails Down)	1.86 m
Overall Length	2.49 m
Overall Width	1.15 m
Wheelbase	1.85 m
Ground Clearance (Stowed)	0.11 m
Ground Clearance	0.02 m
Platform Capacity	350 kg
Capacity on Deck Extension	113 kg
Max. Number of Workers (Indoor/Outdoor)	3/1
Travel Speed (Stowed)	3.5 km/h
Travel Speed (Elevated)	0.8 km/h
Turning Radius (Inside)	0.1 m
Turning Radius (Outside)	2.2 m
Up/Down Drive Motor	24V/3.75KW
Up/Down Time	60s/35s
Gradeability	25% (14°)
Max. Working Slope (Lateral/Vertical)	1.5°/3°
Control	Proportional Control
Drive	Front Wheels
Brakes	Front Wheels
Tire	Ø305mm × 114mm

www.rjc.sa - info@rjc.sa

مؤسسة رمز ركاز الجودة للتجارة
Ramz Rikaz Al Joudah Trading Est.

C.R. No: 7055068394
VAT No: 312849650600003
4620 Street No. 10
3602 Al Jazirah Dist.
Riyadh 14262
Saudi Arabia

السجل التجاري: ٧٠٥٥٠٦٨٣٩٤
الرقم الضريبي: ٣١٢٨٤٩٦٥٠٦٠٠٠٠٣
٤٦٢٠ شارع رقم ١٠
٣٦٠٢ حي الجزيرة
الرياض ١٤٢٦٢
المملكة العربية السعودية

Specification	Value
Battery	135Ah Li-ion
Battery Charger	24V/30A
Operating Weight	1425 kg
Platform Height	11.80 m
Platform Height (Stowed)	1.52 m
Overall Height (Rails Up)	2.65 m
Overall Length	2.40 m
I-Ground Clearance (Stowed)	0.11 m