



www.rjc.sa - info@rjc.sa

# رکاز الجودة للمقاولات العامة Rakaz Al Joudah General Contracting

C.R. No: 2050175808

VAT NO: 301143888700003

7279 Al Khobar Al Janubiyah

5207 Al khobar 34622

Saudi Arabia

السجل التجاري: ٢٠٥٠١٧٥٨٠٨

الرقم الضريبي: ٣٠١١٤٣٨٨٨٧٠٠٠٣

٧٢٧٩ الخبر جنوبية

٥٢٠٧ الخبر ٣٤٦٢٢

المملكة العربية السعودية

## Datasheet

Rental Genie Scissor Lift Model: GS-1932

Brand: Genie



### Short Description

- **Working height:** 7.79 m
- **Platform height:** 5.79 m
- **Lift capacity:** 227 kg



www.rjc.sa - info@rjc.sa

# ركاز الجودة للمقاولات العامة Rakaz Al Joudah General Contracting

C.R. No: 2050175808

السجل التجاري: ٢٠٥٠١٧٥٨٠٨

VAT NO: 301143888700003

الرقم الضريبي: ٣٠١١٤٣٨٨٨٧٠٠٠٣

7279 Al Khobar Al Janubiyah

٧٢٧٩ الخبر جنوبية

5207 Al khobar 34622

٥٢٠٧ الخبر ٣٤٦٢٢

Saudi Arabia

المملكة العربية السعودية

## Full Description

Genie® GS™-1932 Electric Slab Scissor Lift

The Genie GS-1932 is a compact, all-electric slab scissor lift designed for safe, efficient work at height on firm, level surfaces. With quiet operation, a narrow 0.82 m footprint, and the latest AC E-Drive system, it delivers long runtime, low maintenance, and precise control for both indoor and outdoor jobs.

## Key Highlights

- **Working height:** up to 7.85 m indoors (6.47 m outdoors)
- **Capacity:** 227 kg (500 lb) on the main platform; 113 kg (250 lb) on the extension deck
- **Compact & agile:** front-wheel drive with zero inside turning radius; passes through standard doors with rails lowered
- **Large workspace:** 0.91 m roll-out extension deck for extra reach and room for tools
- **Smart operation:** Smart Link™ dual-zone controls, proportional lift/drive, and drive-at-full-height capability
- **Service friendly:** swing-out component trays for quick access; onboard diagnostics
- **Low floor loading & quiet:** <70 dBA sound pressure and compliant vibration levels for facility work

## Typical Applications

- Facilities maintenance and fit-outs
- MEP (mechanical, electrical, plumbing) installation
- Retail, warehousing, and industrial interiors
- Signage, finishing, and inspection tasks

## Power & Drive

- Genie AC **E-Drive** with dual sealed front-wheel electric drive motors for high efficiency and runtime
- Battery options: 24 V flooded lead-acid (4 × 6 V, 210 Ah), AGM maintenance-free, or 24 V 90 Ah lithium-ion
- Hydraulic tank capacity (E-Drive): 3.8 L

## Safety & Compliance

- Smart Link™ dual-zone controls with motion, tilt, and descent alarms
- Platform load-sense system and platform control guard (PCON)
- Pothole protection system; lanyard attachment points
- Drive-enable and proportional lift/drive controls
- Standards: ANSI A92.20 / CSA B354.6 (region-dependent)

## What's Included

- Folding guardrails with half-height swing gate
- Slide-out extension deck, AC power to platform, diamond-plate deck
- Rear recessed charger receptacle and onboard diagnostics

## Images



www.rjc.sa - info@rjc.sa

# رکاز الجودة للمقاولات العامة Rakaz Al Joudah General Contracting

C.R. No: 2050175808

VAT NO: 301143888700003

7279 Al Khobar Al Janubiyah  
5207 Al khobar 34622  
Saudi Arabia

السجل التجاري: ٢٠٥٠١٧٥٨٠٨

الرقم الضريبي: ٣٠١١٤٣٨٨٨٧٠٠٠٠٣

٧٢٧٩ الخبر جنوبية  
٥٢٠٧ الخبر ٣٤٦٢٢  
المملكة العربية السعودية





www.rjc.sa - info@rjc.sa

# ركاز الجودة للمقاولات العامة Rakaz Al Joudah General Contracting

C.R. No: 2050175808

VAT NO: 301143888700003

7279 Al Khobar Al Janubiyah

5207 Al khobar 34622

Saudi Arabia

السجل التجاري: ٢٠٥٠١٧٥٨٠٨

الرقم الضريبي: ٣٠١١٤٣٨٨٨٧٠٠٠٣

٧٢٧٩ الخبر جنوبية

٥٢٠٧ الخبر ٣٤٦٢٢

المملكة العربية السعودية

## Technical Specifications

### Rental Genie Scissor Lift Model: GS-1932

Specification	Value
Manufacturer	Genie
Model Number	GS-1932
Working height maximum	7.79 m
Platform height maximum	5.79 m
Platform length (extended)	2.54 m
Platform length (retracted)	1.63 m
Slide-out platform extension	0.91 m
Platform width (inside)	0.74 m
Guardrail height	1.10 m
Toeboard height	0.15 m
Stowed height (fixed rails)	2.00 m
Stowed height (folding guardrails)	2.11 m
Stowed height (rails folded)	1.75 m
Stowed length	1.83 m
Stowed length (extended)	2.74 m
Width	0.81 m
Wheelbase	1.32 m
Ground clearance (centre)	0.06 m
Ground clearance (pothole guards deployed)	0.02 m
Maximum platform occupancy (indoor)	2
Maximum platform occupancy (outdoor)	1
Lift capacity	227 kg
Drive speed (stowed)	4.0 km/h
Drive speed (raised)	0.8 km/h
Gradeability	30%
Turning radius (outside)	1.55 m
Raise speed	16 sec
Lower speed	25 sec
Power source	24 V (four 6 V 225 Ah batteries)
Hydraulic system capacity	14.2 L
Weight	1500 kg