



www.rjc.sa - info@rjc.sa

رکاز الجودة للمقاولات العامة Rakaz Al Joudah General Contracting

C.R. No: 2050175808

VAT NO: 301143888700003

7279 Al Khobar Al Janubiyah

5207 Al khobar 34622

Saudi Arabia

السجل التجاري: ٢٠٥٠١٧٥٨٠٨

الرقم الضريبي: ٣٠١١٤٣٨٨٨٧٠٠٠٣

٧٢٧٩ الخبر جنوبية

٥٢٠٧ الخبر ٣٤٦٢٢

المملكة العربية السعودية

Datasheet

Rental JCB A45E Electric Articulated Boom Lift

Brand: JCB



Short Description

JCB A45E Electric Articulated Boom Lift delivers zero-emission operation with class-leading performance for indoor and outdoor work.

- **Max platform height:** 13.84 m
- **Horizontal reach:** 7.47 m • **Up-and-over:** 7.48 m
- **Platform capacity:** 300 kg • **Rotation:** 160°
- **Turret rotation:** 355° • **Wind rating:** 12.5 m/s
- **Drive:** 4WD • **Max speed (stowed/raised):** 7.0 / 0.87 km/h
- **Power:** 48 V battery (VISION EVL16-400A-AM, 400 Ah)
- **Tyres:** Foam-filled, non-marking 33×12D610
- **Safety & monitoring:** Electronic crush protection, on-screen diagnostics, JCB LiveLink



www.rjc.sa - info@rjc.sa

رکاز الجودة للمقاولات العامة Rakaz Al Joudah General Contracting

C.R. No: 2050175808

السجل التجاري: ٢٠٥٠١٧٥٨٠٨

VAT NO: 301143888700003

الرقم الضريبي: ٣٠١١٤٣٨٨٨٧٠٠٠٣

7279 Al Khobar Al Janubiyah

٧٢٧٩ الخبر جنوبية

5207 Al khobar 34622

٥٢٠٧ الخبر ٣٤٦٢٢

Saudi Arabia

المملكة العربية السعودية

Full Description

JCB A45E Electric Articulated Boom Lift

The JCB A45E is an all-electric articulated boom designed for productive work indoors and outdoors. It delivers zero emissions, low noise, and confident performance with a 300 kg platform capacity and smooth proportional control.

Highlights

- **Max platform height:** 13.84 m
- **Horizontal reach:** 7.47 m · **Up-and-over:** 7.48 m
- **Platform capacity:** 300 kg · **Platform rotation:** 160°
- **Turret rotation:** 355° · **Wind rating:** 12.5 m/s
- **Drive:** 4WD · **Max speed (stowed/raised):** 7.0 / 0.87 km/h
- **Gradeability:** 40%

Dimensions (stowed)

- **Length:** 7.04 m
- **Width:** 2.26 m
- **Height:** 2.23 m
- **Wheelbase:** 2.03 m
- **Tail swing:** 0.12 m
- **Ground clearance:** 0.31 m
- **Operating weight:** 7,750 kg

Platform

- **Platform size:** 0.84 m (L) × 1.84 m (W)
- **Platform height (entry):** 1.24 m
- **Entry type:** Drop bar · **Entries:** 3
- **Occupancy:** 2 persons
- **Electronic crush protection:** Standard

Power & Electrics

- **System voltage:** 48 V
- **Batteries:** VISION EVL16-400A-AM, 400 Ah
- **Tilt sensor setting:** 5°

Driveline & Steering

- **Drive:** 4WD
- **Steer type:** 2WS
- **Turning radius (inside/outside):** 2.65 m / 4.67 m
- **Max circle (folded):** 5.96 m

Tyres

- **Type:** Foam-filled, non-marking
- **Size:** 33×12D610

Monitoring, Safety & Build

- On-screen diagnostics · JCB LiveLink (Std)
- Electronic crush protection (Std) · Slew lock · Emergency override



www.rjc.sa - info@rjc.sa

ركاز الجودة للمقاولات العامة Rakaz Al Joudah General Contracting

C.R. No: 2050175808

VAT NO: 301143888700003

7279 Al Khobar Al Janubiyah
5207 Al khobar 34622
Saudi Arabia

السجل التجاري: ٢٠٥٠١٧٥٨٠٨

الرقم الضريبي: ٣٠١١٤٣٨٨٨٧٠٠٠٠٣

٧٢٧٩ الخبر جنوبية
٥٢٠٧ الخبر ٣٤٦٢٢
المملكة العربية السعودية

- External hose and harness routing
- Regenerative motors · Function speed control · Oscillating steering axle
- Puncture-proof tyres

All specifications are for the A45E model and may change without notice. Performance can vary with conditions and configuration.

Images





www.rjc.sa - info@rjc.sa

ركاز الجودة للمقاولات العامة Rakaz Al Joudah General Contracting

C.R. No: 2050175808

VAT NO: 301143888700003

7279 Al Khobar Al Janubiyah
5207 Al khobar 34622
Saudi Arabia

السجل التجاري: ٢٠٥٠١٧٥٨٠٨

الرقم الضريبي: ٣٠١١٤٣٨٨٨٧٠٠٠٠٣

٧٢٧٩ الخبر جنوبية
٥٢٠٧ الخبر ٣٤٦٢٢
المملكة العربية السعودية

Technical Specifications

Rental JCB A45E Electric Articulated Boom Lift

Specification	Value
Weight	7750 kg
Length (stowed)	7.04 m
Width (stowed)	2.26 m
Height (stowed)	2.23 m
Wheelbase	2.03 m
Tail swing	0.12 m
Ground clearance	0.31 m
Platform length	0.84 m
Platform width	1.84 m
Platform height	1.24 m
Entry type	Drop bar
Entry number	3
Occupancy	2 persons
Capacity	300 kg
Platform rotation	160°
Electronic crush protection	Standard
Drive	4WD
Max stowed speed	7.0 km/h
Max raised speed	0.87 km/h
Gradeability	40 %
Tyre type	"Foam-filled
Tyre size	33x12D610
System voltage	48 V
Battery make	VISION
Battery model	EVL16-400A-AM
Battery capacity	400 Ah
Tilt sensor setting	5°
Steer type	2WS
Turning radius (inside)	2.65 m
Turning radius (outside)	4.67 m
Max circle in folded position	5.96 m
Platform height (max)	13.84 m



www.rjc.sa - info@rjc.sa

ركز الجودة للمقاولات العامة Rakaz Al Joudah General Contracting

C.R. No: 2050175808

VAT NO: 301143888700003

7279 Al Khobar Al Janubiyah
5207 Al khobar 34622
Saudi Arabia

السجل التجاري: ٢٠٥٠١٧٥٨٠٨

الرقم الضريبي: ٣٠١١٤٣٨٨٨٧٠٠٠٠٣

٧٢٧٩ الخبر جنوبية
٥٢٠٧ الخبر ٣٤٦٢٢
المملكة العربية السعودية

Specification	Value
Horizontal reach	7.47 m
Up-and-over clearance	7.48 m
Turret rotation	355°
Max wind speed	12.5 m/s
Features	"Regenerative motors
Weight	7750 kg
Length (stowed)	7.04 m
Width (stowed)	2.26 m
Height (stowed)	2.23 m
Wheelbase	2.03 m
Tail swing	0.12 m
Ground clearance	0.31 m
Platform length	0.84 m
Platform width	1.84 m
Platform height	1.24 m
Entry type	Drop bar
Entry number	3
Occupancy	2 persons
Capacity	300 kg
Platform rotation	160°
Electronic crush protection	Standard
Drive	4WD
Max stowed speed	7.0 km/h
Max raised speed	0.87 km/h
Gradeability	40 %
Tyre type	"Foam-filled
Tyre size	33x12D610
System voltage	48 V
Battery make	VISION
Battery model	EVL16-400A-AM
Battery capacity	400 Ah
Tilt sensor setting	5°
Steer type	2WS
Turning radius (inside)	2.65 m
Turning radius (outside)	4.67 m
Max circle in folded position	5.96 m



www.rjc.sa - info@rjc.sa

ركز الجودة للمقاولات العامة Rakaz Al Joudah General Contracting

C.R. No: 2050175808

السجل التجاري: ٢٠٥٠١٧٥٨٠٨

VAT NO: 301143888700003

الرقم الضريبي: ٣٠١١٤٣٨٨٨٧٠٠٠٣

7279 Al Khobar Al Janubiyah

٧٢٧٩ الخبر جنوبية

5207 Al khobar 34622

٥٢٠٧ الخبر ٣٤٦٢٢

Saudi Arabia

المملكة العربية السعودية

Specification	Value
Platform height (max)	13.84 m
Horizontal reach	7.47 m
Up-and-over clearance	7.48 m
Turret rotation	355°
Max wind speed	12.5 m/s
Features	&amp;amp;quot;Regenerative motors