



www.rjc.sa - info@rjc.sa

# ركز الجودة للمقاولات العامة Rakaz Al Joudah General Contracting

C.R. No: 2050175808

VAT NO: 301143888700003

7279 Al Khobar Al Janubiyah

5207 Al khobar 34622

Saudi Arabia

السجل التجاري: ٢٠٥٠١٧٥٨٠٨

الرقم الضريبي: ٣٠١١٤٣٨٨٨٧٠٠٠٣

٧٢٧٩ الخبر جنوبية

٥٢٠٧ الخبر ٣٤٦٢٢

المملكة العربية السعودية

## Datasheet

### Komatsu PC200 Excavator for Rent

Brand: Komatsu



#### Short Description

- **Year of manufacture:** 2011
- Rate excludes accommodation, transportation, and diesel
- Transport/mobilization is charged separately and varies by rental period



www.rjc.sa - info@rjc.sa

# ركاز الجودة للمقاولات العامة Rakaz Al Joudah General Contracting

C.R. No: 2050175808

السجل التجاري: ٢٠٥٠١٧٥٨٠٨

VAT NO: 301143888700003

الرقم الضريبي: ٣٠١١٤٣٨٨٨٧٠٠٠٣

7279 Al Khobar Al Janubiyah

٧٢٧٩ الخبر جنوبية

5207 Al khobar 34622

٥٢٠٧ الخبر ٣٤٦٢٢

Saudi Arabia

المملكة العربية السعودية

## Full Description

**2011 Komatsu PC200** hydraulic crawler excavator, 20-ton class, available for short- or long-term rental in KSA. Suits earthworks, trenching, backfilling, and truck loading on civil and infrastructure jobs.

## Key features

- Komatsu SAA6D102E-2, 143 HP net @ 1,950 rpm
- HydraMind load-sensing hydraulics for smooth multi-function control
- 5.7 m boom with 2.9 m or 2.41 m arm options
- Bucket capacity range 0.48–1.53 m<sup>3</sup>; typical GP bucket ~0.8 m<sup>3</sup>
- Travel speeds up to 5.5 km/h; swing speed 12.4 rpm
- Operating weight ~20 t for stable digging and lifting

## Attachments and setup

- GP bucket as standard
- Other buckets and breaker piping subject to availability
- 700 mm or 800 mm triple-grouser shoes depending on site conditions

## Rental scope and terms

- Rate excludes accommodation, transportation, and diesel
- Transport/mobilization is charged separately and varies by rental period
- Operator, fuel service, and preventive maintenance packages available on request
- Daily, weekly, and monthly plans supported

## Ideal applications

- Excavation, trenching for utilities, footing preparation, stockpile handling, and general site prep

## Notes

- Year of manufacture: 2011
- Detailed spec sheet and lifting charts available on request
- Units are delivered inspected and ready for site deployment

## Images





www.rjc.sa - info@rjc.sa

# ركاز الجودة للمقاولات العامة Rakaz Al Joudah General Contracting

C.R. No: 2050175808

VAT NO: 301143888700003

7279 Al Khobar Al Janubiyah  
5207 Al khobar 34622  
Saudi Arabia

السجل التجاري: ٢٠٥٠١٧٥٨٠٨

الرقم الضريبي: ٣٠١١٤٣٨٨٨٧٠٠٠٠٣

٧٢٧٩ الخبر جنوبية  
٥٢٠٧ الخبر ٣٤٦٢٢  
المملكة العربية السعودية

## Technical Specifications

### Komatsu PC200 Excavator for Rent

Specification	Value
Manufacturer	Komatsu
Model number	PC200-7
Country of origin	Japan
Machine type	Hydraulic crawler excavator
Operating weight (700 mm shoes)	&quot;19
Operating weight (800 mm shoes)	&quot;20
Engine model	Komatsu SAA6D102E-2
Engine type	&quot;6-cyl
Displacement	5.88 L
Power (net)	106.6 kW (143 HP) @ 1950 rpm
Power (gross)	111.9 kW (150 HP) @ 1950 rpm (SAE J1995)
Rated speed	1950 rpm
Emissions	EPA Tier 2
Hydraulic system	&quot;HydrauMind closed-center
Working modes	&quot;4 modes: A (Active)
Main pump max flow	428 L/min (113 US gpm)
Relief pressures	Implement 37.3 MPa; Travel 37.3 MPa; Swing 28.9 MPa; Pilot 3.2 MPa
Travel speeds (auto 3-speed)	5.5 / 4.1 / 3.0 km/h
Max drawbar pull	178 kN
Gradeability	70% (35°)
Swing speed	12.4 rpm
Boom length	5.7 m
Arm length options	2.410 m or 2.925 m
Bucket capacity range	0.48 – 1.53 m <sup>3</sup> (0.63 – 2.0 yd <sup>3</sup> )
Bucket digging force (Power Max)	SAE 138 kN; ISO 149 kN
Arm crowd force (Power Max)	2.410 m arm: 124–127 kN; 2.925 m arm: 101–108 kN
Max digging depth	&quot;6
Max reach at ground	&quot;9
Max dumping height	&quot;6
Fuel capacity	400 L
Hydraulic tank capacity	143 L
Cooling system capacity	22.4 L



www.rjc.sa - info@rjc.sa

# ركاز الجودة للمقاولات العامة

## Rakaz Al Joudah General Contracting

C.R. No: 2050175808

VAT NO: 301143888700003

7279 Al Khobar Al Janubiyah

5207 Al khobar 34622

Saudi Arabia

السجل التجاري: ٢٠٥٠١٧٥٨٠٨

الرقم الضريبي: ٣٠١١٤٣٨٨٨٧٠٠٠٠٣

٧٢٧٩ الخبر جنوبية

٥٢٠٧ الخبر ٣٤٦٢٢

المملكة العربية السعودية

Specification	Value
Engine oil capacity	24.0 L
Swing drive oil	6.6 L
Final drive oil (each)	4.5 L
Undercarriage	X-frame; box-section track frames; sealed tracks; hydraulic adjusters
Shoe width options	700 mm or 800 mm triple-grouser
Overall length	&quot;9
Overall width	&quot;3
Cab height	&quot;3
Ground clearance (counterweight / min)	&quot;1
Tail swing radius	&quot;2
Track length on ground	&quot;3
Track gauge	&quot;2
Rollers per side	Track rollers: 7; Carrier rollers: 2
Standard equipment (abridged)	A/C with defroster; Auto-Decel; engine warm-up; water separator; double-element air cleaner; 50 A alternator; 24 V starter; boom/arm holding valves; multi-function color monitor; PPC pilot controls; counterweight; fan guard; travel alarm; RH boom and cab
Optional equipment (examples)	2.410 m or 2.925 m arms (std/HD with piping); 5.7 m boom (std/HD with piping); 700 mm shoes; cab guards; sun/rain visors; high-ambient spec; full-length track roller guards; 12 V converter; track frame undercover