



www.rjc.sa - info@rjc.sa

# رکاز الجودة للمقاولات العامة Rakaz Al Joudah General Contracting

C.R. No: 2050175808

VAT NO: 301143888700003

7279 Al Khobar Al Janubiyah

5207 Al khobar 34622

Saudi Arabia

السجل التجاري: ٢٠٥٠١٧٥٨٠٨

الرقم الضريبي: ٣٠١١٤٣٨٨٨٧٠٠٠٣

٧٢٧٩ الخبر جنوبية

٥٢٠٧ الخبر ٣٤٦٢٢

المملكة العربية السعودية

## Datasheet

### Platform Basket Spider 22.10 Tracked Spider Lift for Rental

Brand: Platform Basket



#### Short Description

Platform Basket Spider 22.10 (ED) tracked spider lift for rental, delivering up to 21.7 m working height with 10.3 m outreach, 230 kg basket capacity, and compact access width of just 0.98 m. Hybrid diesel + 24V electric drive with 365° rotation and narrow/wide outrigger stabilization for confined job sites.



www.rjc.sa - info@rjc.sa

# ركاز الجودة للمقاولات العامة Rakaz Al Joudah General Contracting

C.R. No: 2050175808

السجل التجاري: ٢٠٥٠١٧٥٨٠٨

VAT NO: 301143888700003

الرقم الضريبي: ٣٠١١٤٣٨٨٨٧٠٠٠٣

7279 Al Khobar Al Janubiyah

٧٢٧٩ الخبر جنوبية

5207 Al khobar 34622

٥٢٠٧ الخبر ٣٤٦٢٢

Saudi Arabia

المملكة العربية السعودية

## Full Description

### Platform Basket Spider 22.10 (ED) — Tracked Spider Lift for Rental

The Platform Basket Spider 22.10 (ED) is a compact tracked spider lift designed for safe access at height in tight or restricted work areas. With a maximum working height of **21.70 m**, platform height of **19.70 m**, and maximum outreach of **10.30 m**, it is ideal for maintenance, façade works, MEP installations, and indoor/outdoor applications where access width and ground conditions are critical.

#### Key Performance

- **Working height:** 21.70 m
- **Platform height:** 19.70 m
- **Max outreach:** 10.30 m
- **Basket capacity:** 230 kg
- **Turret rotation:** 365°
- **Basket rotation:** 90° + 90°
- **Basket size (aluminium):** 1.50 x 0.70 m

#### Hybrid ED Powertrain

Your unit is the **ED version**, combining a diesel engine for reliable site power with a **24V DC electric traction system** for controlled maneuvering.

- **Diesel engine:** Kubota Z602, 14 HP @ 3600 rpm
- **Electric traction motor:** 24 Vdc, 7.4 CV / 5.5 kW
- **Travel speed (ED):** up to 1.5 km/h

#### Compact Transport & Access

- **Minimum closed width:** 0.98 m
- **Minimum closed height:** 2.06 m
- **Closed length:** 5.97 m (5.28 m with basket disassembled)
- **Operating weight (ED):** 3260 kg

#### Stabilization for Confined Sites

Multiple stabilizer configurations allow safe setup even in narrow areas while maintaining performance.

- **Wide footprint:** 3.87 x 3.94 m
- **Narrow footprint:** 2.57 x 5.05 m
- **Max horizontal inclination:** 16° (29%)
- **Max side inclination:** 17° (31%)

#### Operational Advantages

- Radio remote control for positioning and setup
- Triple stabilization with automatic outreach control
- Multi-width stabilizer settings for restricted spaces
- Air / water / 220 Vac outlets available in the basket (as per configuration)
- Optional interchangeable cage with winch capability (optional)

Contact us to confirm availability, delivery to site, and rental terms for your project.



www.rjc.sa - info@rjc.sa

# رکاز الجودة للمقاولات العامة Rakaz Al Joudah General Contracting

C.R. No: 2050175808

VAT NO: 301143888700003

7279 Al Khobar Al Janubiyah

5207 Al khobar 34622

Saudi Arabia

السجل التجاري: ٢٠٥٠١٧٥٨٠٨

الرقم الضريبي: ٣٠١١٤٣٨٨٨٧٠٠٠٣

٧٢٧٩ الخبر جنوبية

٥٢٠٧ الخبر ٣٤٦٢٢

المملكة العربية السعودية

## Images





www.rjc.sa - info@rjc.sa

# ركاز الجودة للمقاولات العامة Rakaz Al Joudah General Contracting

C.R. No: 2050175808

VAT NO: 301143888700003

7279 Al Khobar Al Janubiyah  
5207 Al khobar 34622  
Saudi Arabia

السجل التجاري: ٢٠٥٠١٧٥٨٠٨

الرقم الضريبي: ٣٠١١٤٣٨٨٨٧٠٠٠٠٣

٧٢٧٩ الخبر جنوبية

٥٢٠٧ الخبر ٣٤٦٢٢

المملكة العربية السعودية

## Technical Specifications

### Platform Basket Spider 22.10 Tracked Spider Lift for Rental

Specification	Value
Manufacturer	Platform Basket
Country of Origin	Italy
Model Number	Spider 22.10
Equipment Type	Tracked spider lift / aerial work platform
Available Versions	STD / E / ED
Maximum Working Height	21.70 m
Platform Height (Floor Height)	19.70 m
Maximum Side Outreach	10.30 m
Tower Rotation	365°
Basket Dimensions (Aluminium)	1.50 x 0.70 m
Basket Rotation	90° + 90°
Platform Capacity	230 kg
Closed Length (basket disassembled)	5.97 m (5.28 m)
Closed Width (Minimum)	0.98 m
Closed Height (Minimum)	2.06 m
Stabilization Footprint (Wide)	3.87 x 3.94 m
Stabilization Footprint (Narrow)	2.57 x 5.05 m
Maximum Horizontal Inclination	16° (29%)
Maximum Side Inclination	17° (31%)
Maximum Travel Speed (STD)	1.5 km/h
Maximum Travel Speed (E)	0.8 km/h
Maximum Travel Speed (ED)	1.5 km/h
Operating Weight (STD)	2980 kg
Operating Weight (E)	3260 kg
Operating Weight (ED)	3260 kg
Ground Pressure, Stowed (STD)	2.94 kN/m <sup>2</sup>
Ground Pressure, Stowed (E)	3.21 kN/m <sup>2</sup>
Ground Pressure, Stowed (ED)	3.21 kN/m <sup>2</sup>
Ground Pressure, On Stabilizers (STD)	1.91 kN/m <sup>2</sup>
Ground Pressure, On Stabilizers (E)	2.09 kN/m <sup>2</sup>
Ground Pressure, On Stabilizers (ED)	2.09 kN/m <sup>2</sup>
Max Point Load on One Stabilizer (STD)	21 kN



www.rjc.sa - info@rjc.sa

# ركاز الجودة للمقاولات العامة Rakaz Al Joudah General Contracting

C.R. No: 2050175808

السجل التجاري: ٢٠٥٠١٧٥٨٠٨

VAT NO: 301143888700003

الرقم الضريبي: ٣٠١١٤٣٨٨٨٧٠٠٠٣

7279 Al Khobar Al Janubiyah

٧٢٧٩ الخبر جنوبية

5207 Al khobar 34622

٥٢٠٧ الخبر ٣٤٦٢٢

Saudi Arabia

المملكة العربية السعودية

Specification	Value
Max Point Load on One Stabilizer (E)	23 kN
Max Point Load on One Stabilizer (ED)	23 kN
Diesel Engine (STD)	Kubota Z602 — 14 HP @ 3600 rpm
Diesel Engine (ED)	Kubota Z602 — 14 HP @ 3600 rpm
Electric Motor 220 Vac (STD)	3 CV / 2.2 kW
Electric Motor 220 Vac (E)	3 CV / 2.2 kW
Electric Motor 24 Vdc (E)	7.4 CV / 5.5 kW
Electric Motor 24 Vdc (ED)	7.4 CV / 5.5 kW
Traction Battery 24Vdc Lead Acid (E)	2 x 210 Ah
Traction Battery 24Vdc Lead Acid (ED)	400 Ah
Traction Battery 24Vdc Lithium Ion (E)	1 x 210 Ah
Traction Battery 24Vdc Lithium Ion (ED)	300 Ah
Battery Charger, Lead Acid (E/ED)	45 Ah
Battery Charger, Lithium Ion (E/ED)	100/50 Ah
Key Features	Radio remote control; triple stabilization with automatic outreach; multi-width stabilizer settings; air/water/220 Vac outlets in basket; optional interchangeable cage with winch; hybrid version on request.